

Kindly amend the claims as follows.

1-28. (canceled)

29. (currently amended) ~~A method for the initialisation~~initialization of mobile data carriers (IM) with assigned ~~decentralised~~decentralized read and write stations (WR) and/or of ~~decentralised~~decentralized read and write stations (WR) within the framework of an ~~authorisation~~authorization system (A), ~~wherein characterised in that by an authorisation with~~authorisation means (AM) at an authorisation authority (HA) in a secure environment (g) ~~initialisation~~initialization data (DI, A-I, I-I) are generated ~~and transmitted throughin an authorization process in a secure environment (g) at an authorization authority (HA) by means of authorization means (AM) and said initialization data are sent over~~ a network (N) in a secure communication ~~and with~~according to security rules corresponding to the ~~authorisation~~authorization system to a ~~decentralised~~decentralized ~~authorised~~authorized read and write station (A-WR) ~~and wherein where~~ the mobile data carriers (IM) are ~~correspondingly~~ initialized (IMj) with the ~~initialisation~~initialization data (DI) ~~at the read and write station (A-WR).~~ and/or that the ~~initialisation~~initialization data (DI) are ~~transmitted through~~sent over the network (N) to a ~~decentralised~~decentralized read and write station (WR), by means of which the read and write station is ~~initialised~~initialized (WRk).

30. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised in that wherein~~ the ~~authorisation~~authorization authority (HA) is formed by a host computer (H) or by a remote ~~authorisation~~authorization read and write station (R-A-WR).

31. (currently amended) ~~The method~~Method according to claim 29, ~~characterised in that wherein~~ the ~~authorisation~~authorization means (AM) are ~~formed by~~consisting of special ~~authorisation~~authorization identification media (AM-IM) or ~~by of~~ ~~authorisation~~authorization data (AM-I).

32. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised in that wherein~~ a (non-~~authorised~~authorized) ~~decentralised~~decentralized read and write

station (WR) ~~is first of all~~ transformed into an ~~authorised~~authorized read and write station (A-WR) by means of function ~~authorisation~~authorization data (A-I-FA) which are contained in the ~~initialisation~~initialization data (DI), and which subsequently is capable of ~~initialising~~initializing mobile data carriers (IM) in correspondence with the ~~initialisation~~initialization data.

33. (currently amended) ~~The m~~The method according to claim 29, characterised in that~~wherein~~ within the framework of the ~~authorisation~~authorization system (A) several ~~authorisation~~authorization authorities (HAi) with the same and/or with differing ~~authorisation~~authorization levels (OLi) are provided.

34. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised in that~~wherein several ~~authorisation~~authorization means (AMi) with the same and/or with differing ~~authorisation~~authorization levels (OLi) are provided.

35. (currently amended) ~~The m~~The method according to claim 29, characterised in that~~wherein~~ ~~initialisation~~initialization data (DI, A-I, I-I) are ~~sent~~transmitted to the ~~authorised~~authorized read and write stations (A-WR), ~~resp., or to the decentralised~~decentralized read and write stations (WR) through more than one network level (N1, N2) and/or through more than one ~~authorisation~~authorization authority (HA1, HA2).

36. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised in that~~wherein the ~~initialisation~~initialization data (DI) are ~~transmitted through~~sent over a secure private network (Np).

37. (currently amended) ~~The m~~The method according to claim 29, characterised in~~wherein~~ the ~~initialisation~~initialization data are ~~sent over~~transmitted through an open public network (No) with an encryption and security gates on both sides (G1, G2).

38. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised in that~~wherein with the ~~initialisation~~initialization data (DI2.2) application extensions (App2.2) are ~~initialised~~initialized.

39. (currently amended) ~~The m~~Method according to claim 29, ~~characterised in that~~wherein with the ~~initialisation~~initialization data (DI3) new independent applications (App3) are ~~initialised~~initialized.

40. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised in that~~wherein in a blank mobile data carrier which is prepared with a system data field (CDF) applications (App) are newly ~~initialised~~initialized with the ~~initialisation~~initialization data (DI).

41. (currently amended) ~~The m~~Method according to claim 29, ~~characterised in that~~wherein ~~through the network (N) a permanent connection over the network (N) is made between the~~ through the network (N) a permanent connection over the network (N) is made between the ~~authorisation~~authorization authority (HA) and the ~~decentralised~~decentralized read and write station (A-WR, WR)~~is in existence~~.

42. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised in that~~wherein ~~at the connection between the~~ at the connection between the ~~authorisation~~authorization authority (HA) and the ~~decentralised~~decentralized read and write stations (A-WR, WR) over through the network (N) is only ~~in existence~~ made occasionally and ~~that~~ when it is an exchange of data takes place.

43. (currently amended) ~~The m~~Method according to claim 29, ~~characterised in that~~wherein for the ~~initialisation~~initialization a user ~~authorisation~~authorization (aw) is effected by the read and write station (A-WR, WR), ~~resp., or by its owner (12) and/or that an identification~~ resp., or by its owner (12) and/or that an identification ~~authorisation~~authorization means (ID-AM) is ~~required~~necessary.

44. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised in that~~wherein for an ~~initialisation~~initialization a user ~~authorisation~~authorization (ai) by through the data carrier, ~~resp., or by~~ the owner (13) of the data carrier takes place.

45. (currently amended) ~~The m~~Method according to claim 29, ~~characterised in that~~wherein for the ~~authorisation~~authorization of ~~initialisation~~initializations over through the network (N), as well as for the execution of applications at the read and write station (A-WR, WR), ~~resp., at the data carrier (IM) personal data (aw) of the owner of the read and write station or, resp., personal data (ai) of the owner of~~

the data carrier, such as a PIN code or biometric data, are made use of ~~used as~~
~~authorisation~~authorization means.

46. (currently amended) ~~Method in accordance with~~The method according to claim 29,
~~characterised in that~~wherein the mobile data carriers (IM) comprise an applications micro-processor
(AppuP) for the processing of applications program data (I-I-Cod).

47. (currently amended) ~~The m~~Method according to claim 29, ~~characterised in that~~wherein the data
carriers (IM) are designed as contact-less, active or passive identification media.

48. (currently amended) ~~Method in accordance with~~The method according to claim 29, ~~characterised~~
~~in that~~wherein the mobile data carriers (IM), ~~the authorisation~~authorization identification media (AM-
IM) and ~~the identification~~ authorization media (ID-AM) are formed by the same mobile
data carriers.

49. (currently amended) ~~The m~~Method according to claim 29, ~~characterised in that~~wherein status
informations (S-I) concerning events at the ~~authorised~~authorized, resp. or at the
~~decentralised~~decentralized read and write stations (A-WR, WR) and/or at the mobile data carriers (IM)
~~is announced~~are sent to a corresponding ~~authorisation~~authorization authority (HA) ~~through~~over the
network (N).

50. (currently amended) ~~Method in accordance with~~The method according to claim 49,
~~characterised in that~~wherein the status informations (S-I) ~~are~~is utilized for usage or licensee fee
debiting.

51. (currently amended) ~~The m~~Method according to claim 29, ~~characterised in that~~wherein every
new ~~initialisation~~initialization of a data carrier (IM) for the purpose of debiting a usage or licence fee
is ~~announced~~sent to the ~~authorisation~~authorization authority (HA) ~~through~~over the network (N).

52. (currently amended) ~~Method in accordance with~~The method according to claim 29,
~~characterised in that~~wherein every usage of an application at a decentralized read and write station

(WR) for the purpose of debiting a usage or licensee fee is ~~sent announced~~ to the ~~authorisation~~authorization authority (HA) ~~over~~through the network (N).

53. (currently amended) ~~The m~~Method according to claim 29, ~~characterised in that~~wherein a multi-level ~~initialisation~~initialization of the data carriers (IM) ~~throughover~~ networks (N) is provided, which is effected in hierarchically graduated steps within the framework of the ~~authorisation~~authorization system (A).

54-56. (canceled)

57. (new) A mobile data carrier (IMj) for the communication with assigned decentralized read and write stations (WR, WRk) within the frame of an authorization system (A), said mobile data carrier comprising initialization data (DI, A-I, I-I), wherein said initialization data (DI, A-I, I-I) are generated in an authorization process in a secure environment (g) at an authorization authority (HA) by means of authorization means (AM) and said initialization data are sent over a network (N) in a secure communication according to security rules corresponding to the authorization system (A) to a decentralized authorized read and write station (A-WR) where the mobile data carrier is initialized (IMj) with the initialization data.

58. (new) A read and write station (WRk) for the communication with assigned mobile data carriers (IM, IMj) within the frame of an authorization system (A), said read and write station comprising initialization data (DI, A-I, I-I) wherein said initialization data (DI, A-I, I-I) are generated in an authorization process in a secure environment (g) at an authorization authority (HA) by means of authorization means (AM) and said initialization data are sent over a network (N) in a secure communication according to security rules corresponding to the authorization system (A) to a decentralized read and write station (WR) by means of which the read and write station is initialized (WRk).